

2-Way Radio Callbox XD Series

NXDN™ Digital/Analog

Put Communication Right Where You Need It!

Position the XD Series digital radio callbox virtually anywhere to maximize manpower efficiency, improve safety or service response times. Deploys easily — no wires, no trenching, no construction required. Can be used stand-alone using alkaline batteries or can be powered using external AC adapter. The XD Series callbox provides crisp, clear, long range voice communication and allows staff and visitors to communicate with your radio-equipped personnel from points near and far, be it the plant floor, a maintenance garage, the gated entrance, a delivery dock or the 9th Tee.



Features / **Benefits:**

- Wireless, Push-To-Talk, 2-Way, NXDN Digital or Analog Technology
No Costly Trenching or Construction Costs To Install. Allows Easy System Migration from Analog To Digital
- Enhanced Digital Performance, Business Band Frequencies
Long Range — Up to 1 Mile*, Line-Of-Sight. Works with Any Other NXDN Digital or Analog Business Band 2-Way Radio.
- Rugged, High-Impact Gasket Sealed Enclosure
Durable, Sealed and Weatherproof For Outdoor Use
- Internal Antenna, Tough, Machined Aluminum PTT Button
Long-Life, Tamper and Vandal-Resistant
- Battery Powered or External Power Capable
No Wires, Stand Alone Operation or Can Be Externally Powered with Optional AC Adapter For Always-On Operation
- High Audio Output Capability
Adjustable Volume - Loud, Easy To Hear In Loud Environments
- PC Programmable and User Adjustable Settings
Allows Easy, In-The-Field Programming
- Recordable Voice Messages
Automatic Messages Increase System Usefulness
- Built-In Relay Control (7 series models only)
Allows Long-Range, Remote Control Of Gates Or Doors
- Standard Flange Mount Hole Pattern
Easy Installation. Optional Mounting Brackets Available
- Choice of 2 Enclosure Colors
Pick The Color Best Suited To Meet Your Need:
-High Visibility Green and Coal Black
-Custom Colors Available For Volume App



Applications... Schools and Day Cares • Manufacturing and Construction Sites • Health Care Facilities • Delivery Docks • Gate Secured Areas • Amusement Parks and Resorts



Analog Compatible Ritron Products...



Accessories...



Models	Description - Analog/NXDN Digital	TX Pwr Using 3 D-Cells	TX Pwr Using Ext 12VDC Pwr	(7 Series) Includes Built-In Relay, Stored-Voice Msg, Sensor Switch Inputs
RQX-117NX	VHF, 150-160 MHz, Part 90 Freqs, Hi-Viz Green Housing	700mW	2 Watts	Yes
RQX-117NX-BLK	VHF, 150-160 MHz, Part 90 Freqs, Black Housing	700mW	2 Watts	Yes
RQX-417NX	UHF, 450-470 MHz, Part 90 Freqs, Hi-Viz Green Housing	700mW	2 Watts	Yes
RQX-417NX-BLK	UHF, 450-470 MHz, Part 90 Freqs, Black Housing	700mW	2 Watts	Yes
No. of RF Channels: 1 Channel NXDN Digital (12.5 or 6.25KHz) or Analog (12.5KHz)				
Signaling-Analog Mode: CTCSS/DCS Encode/Decode Codes, DTMF and Selcall Encode/Decode, 2 Tone Decode				
Signaling-NXDN Digital Mode: 64 Radio Access Numbers (RAN), Subscriber Unit ID (SUID), Destination ID (Individual & Group Selective Call, All-Call)				
Dimensions: 7" H x 5" W x 3" D				
Weight: 2.75 lbs				
Enclosure Material: Gasket Sealed, High-Impact Polycarbonate				
Colors: Black or High-Viz Green				
Environmental: Splash resistant, shock and vibration per Ritron test				
Operating Temperature: -20°C to +55°C (-4°F to 131°F) Battery rating. At 0°C the capacity is < 50% rated) Talk range will decrease at low temperatures when operating on alkaline batteries.				
Programming: Field programming capability of limited parameters. Full programming capability using internal USB Connector used for full PC Programming.				
Remote Control Relay : (7 Series) Can be used to remotely control gates, doors or strobe light. Relay switch is controlled when callbox receives the pre-programmed selective signaling command code. SPDT, 3A, 125VAC/30VDC – Normally Open or Normally Closed (NO Default). Modes of Operation: Momentary or Toggle, On/Off.				
Aux Sensor Monitoring Input: (7 Series) Optional sensors used to detect motion, gate movement, vandal/tamper or vehicle presence can be connected to the callbox using the sensor input. Sensor input responds to an Open or Closed switch. Callbox will send either an alarm tone or a recordable voice message when optional switch/sensor detects a change. Can also be programmed to automatically turn callbox ON and transmits recordable voice message or alarm tone to radios monitoring callbox activity.				
Adjustable Speaker Volume: Adjustable 20% to 100%				
Automatic Turn-Off Feature: Conserves batteries. Selectable turn-off times will automatically turn callbox off after a set period of inactivity on the radio channel. Auto Turn-OFF feature must be enabled when using battery only power.				
Listen-In Feature: Callbox can be selectively paged to allow remote monitoring of audio in the vicinity of the callbox.				
Busy Channel TX Inhibit: Prevents Callbox from transmitting if someone else is using the radio channel.				
Recordable Voice Messages				
1. Greeting Message: 12 sec length max, for benefit of visitor, plays only on the callbox speaker when the On/PTT button is 1st pressed.				
2. Send Call Alert Message: 4 sec length max, transmitted to radios monitoring callbox activity when On/PTT button is 1st pressed.				
3. Send Sensor ON Message: 4 sec length max, transmitted to radios monitoring callbox activity when the Sensor Input goes low.				
4. Send Sensor OFF message: 4 sec length max, transmitted to radios monitoring callbox activity when the Sensor Input goes high.				
5. Send Low Battery Message: 4 sec length max, transmitted to radios monitoring callbox activity when low battery is detected.				
6. Send Power Fail Message: 4 sec length max, transmitted to radios monitoring callbox activity when loss of External 12 VDC is detected.				
Automatic Voice Message "Re-Send": When Alert message from Callbox is not immediately answered, Alert message will automatically be "re-sent" up to 5 times. Selectable 0-5 times.				
Battery Life**				
3 D-Cell Batteries: Alkaline (Ritron recommends Energizer brand cells)				
Number of Transmissions: Approximately 8,000 based on duty cycle stated below				
Duty Cycle: 3 seconds receive, 3 seconds transmit, 10 seconds standby				

*Actual range may be reduced by man-made obstructions, foliage, or terrain.

**Each callbox application is unique, to compute the expected battery life of your callbox application, visit the Ritron Battery Life Calculator at www.ritron.com/BLcalculator.

Go Beyond Normal Limits...™

RITRON
WIRELESS SOLUTIONS

Call 808-845-7827 or visit
www.Starcommwireless.com

About Ritron Inc. - Founded in 1977, Ritron, Inc., is a U.S. company specializing in the design and manufacture of RF wireless voice and data communication products. It offers wireless solutions for commercial, industrial, military, OEM and integrator markets.